



**GRIFFIN GTB341S4MA**



---

**TECH SPECIFICATIONS**

|                                    |                               |
|------------------------------------|-------------------------------|
| <b>MODEL</b>                       | GTB341S4MA                    |
| <b>FUEL PORT</b>                   | 7/8-14" UNF                   |
| <b>FLOW RATE</b>                   | <b>341 LPH / 90 GPH</b>       |
| <b>SERVICE CLEARANCE</b>           | 127 mm                        |
| <b>HEIGHT</b>                      | 412 mm                        |
| <b>WIDTH</b>                       | 145 mm                        |
| <b>DEPTH</b>                       | 160 mm                        |
| <b>NET WEIGHT</b>                  | 2.2 kg                        |
| <b>TEMPERATURE</b>                 | -20 °C / +121 °C              |
| <b>CLEAN PRESURE DROP</b>          | 2.4 kPa                       |
| <b>MAX. OPERATING PRESSURE</b>     | 103 kPa                       |
| <b>CROSS REFERENCE</b>             | 900MA / G900S4MA              |
| <b>REPLACEMENT ELEMENT</b>         | GTB34-2 / GTB34-10 / GTB34-30 |
| <b>CLEAR BOWL FOR GASOLINE USE</b> | PCB36MGA                      |
| <b>HEAT DEFLECTOR SHIELD</b>       | PHDS36MA                      |

Griffin Group International Pte Ltd | [info@griffinfilter.com](mailto:info@griffinfilter.com)