



**GRIFFIN GTB681DM**



---

**TECH SPECIFICATIONS**

<b>MODEL</b>	GTB681DM
<b>FUEL PORT</b>	7/8 – 14" UNF
<b>FLOW RATE</b>	<b>1363 LPH / 360 GPH</b>
<b>SERVICE CLEARANCE</b>	254 mm
<b>HEIGHT</b>	542 mm
<b>WIDTH</b>	476 mm
<b>DEPTH</b>	279 mm
<b>NET WEIGHT</b>	12.6 kg
<b>TEMPERATURE</b>	-20 °C / +121 °C
<b>CLEAN PRESURE DROP</b>	25.5 kPa
<b>MAX. OPERATING PRESSURE</b>	103 kPa
<b>HEAT DEVICE</b>	Optional Parameters
<b>WATER PROBE</b>	Optional Parameters
<b>CROSS REFERENCE</b>	75/1000FHX / G1000DM
<b>REPLACEMENT ELEMENT</b>	<b>GTB68-2 / GTB68-10 / GTB 68-30</b>
	2020SM / 2020TM / 2020PM
<b>CLEAR BOWL</b>	PCB36-2GA

Griffin Group International Pte Ltd | [info@griffinfilter.com](mailto:info@griffinfilter.com)