



**GRIFFIN GTB681TM-S4MA**



---

**TECH SPECIFICATIONS**

<b>MODEL</b>	GTB681TM-S4MA
<b>FUEL PORT</b>	3/4" NPT
<b>FLOW RATE</b>	<b>2043 LPH / 540 GPH</b>
<b>SERVICE CLEARANCE</b>	254 mm
<b>HEIGHT</b>	525 mm
<b>WIDTH</b>	585 mm
<b>DEPTH</b>	313 mm
<b>NET WEIGHT</b>	26.6 kg
<b>TEMPERATURE</b>	-20 °C / +121 °C
<b>CLEAN PRESURE DROP</b>	25.5 kPa
<b>MAX. OPERATING PRESSURE</b>	103 kPa
<b>HEAT DEVICE</b>	Optional Parameters
<b>WATER PROBE</b>	Optional Parameters
<b>CROSS REFERENCE</b>	79/1000MAV / G1000TMS4-MA
<b>REPLACEMENT ELEMENT</b>	GTB68-2 / GTB68-10 / GTB 68-30
<b>CLEAR BOWL FOR GASOLINE USE</b>	PCB36MGA
<b>HEAT DEFLECTOR SHIELD</b>	PHDS36MA

Griffin Group International Pte Ltd | [info@griffinfilter.com](mailto:info@griffinfilter.com)